


SUCCESSFUL TREATMENT OF DIOXIN USING THERMAL CONDUCTION HEATING

Results and Lessons Learned from a First of its Kind Project

Jim Galligan, Gorm Heron, Rich Michalewich, Alyson Fortune, Stan Walker (TerraTherm, Inc., Gardner, MA, USA)
Glenn Anderson, Timothe Burdett, Dzung Tran (TerraTherm, Inc., Danang, Vietnam)



IPTD Pile Construction



Phase 2

Location	Dioxin Concentration (TEQ ppt/g [ppt])	Dioxin Concentration (TEQ ppt/g [ppt])
Phase 1 IPTD samples, 0-1m	51.5	0.198
IPTD, sub-decision unit A, 0-1m	95.6	95% UCL
IPTD, sub-decision unit B, 0-1m	36.3	0.212
IPTD, sub-decision unit C, 0-1m	91	0.243
IPTD, sub-decision unit D, 0-1m	1.9	0.237
		0.198
IPTD, sub-decision unit E, 0-1m	2.4	0.199
IPTD, sub-decision unit F, 0-1m	1.1	0.197
IPTD, sub-decision unit G, 0-1m	16	0.194
IPTD, sub-decision unit H, 0-1m	143	0.199
Phase 1 IPTD samples, 1-2m	0.332	0.195
Phase 1 IPTD samples, 2-3m decision unit, triplicate	0.237	0.191
	2.34	0.199
Phase 1 IPTD samples, 3-4m	0.304	
Phase 1 IPTD samples, 4-5m	0.0918	
Phase 1 IPTD samples, 5-6m	0.981	
Phase 1 IPTD samples, 2-3m decision unit, replicate	0.264	
	0.234	
Mean Post-treatment Phase 1 IPTD	8.9	

Post-Treatment Results


- Ph 1: >90–97% DRE
- Ph 2: >99.99% DRE
- All samples below 150 ppt TEQ goal

ISTD & IPTD Technology

Demonstrated to successfully treat dioxins, PCBs, pesticides and other POPs .

For more information, please contact TerraTherm: Jim Galligan, jgalligan@terratherm.com

Time & Temperature Ensure Results





IPTD Treatment at 335°C

- 87,000 m³ soil
- Treated in 2 phases
- Target: 325°C, 21 days
- Goal: 150 ppt TEQ Dioxin



Extensive Monitoring

- > 450 temperature sensors
- Vapor/liquid effluent monitoring
- Post-treatment hot soil sampling



Acknowledgements



The Danang Airbase project was funded by USAID and USAID has approved TerraTherm's use of project data for this presentation.